



TL07 Series

- Inductance range : 14 ~ 498 μ H
- Current range : 1 ~ 10A
- Sleeved with UL-approved heat shrinkable tube
- Custom-made inductors are available upon request

Part Number	Inductance (μ H, $\pm 10\%$)	DCR (m Ω , max.)	Rated Current (A, max.)	Dimension (mm)			
				A (± 2.0)	B (max.)	C (ref.)	D (± 0.1)
TL07-001	111	315	1	16.0	11.0	14.0	$\varnothing 0.4$
TL07-002	498	720	1	20.0	12.0	18.0	$\varnothing 0.4$
TL07-003	194	400	1	20.0	11.0	18.0	$\varnothing 0.4$
TL07-004	52	110	2	15.0	12.5	13.0	$\varnothing 0.6$
TL07-005	241	250	2	20.0	14.0	18.0	$\varnothing 0.6$
TL07-006	92	140	2	20.0	11.5	18.0	$\varnothing 0.6$
TL07-007	67	90	3	20.0	12.0	18.0	$\varnothing 0.7$
TL07-008	28	45	4	16.0	13.0	13.0	$\varnothing 0.8$
TL07-009	54	60	4	20.0	13.0	18.0	$\varnothing 0.8$
TL07-010	256	160	4	25.0	16.0	23.0	$\varnothing 0.8$
TL07-011	273	160	4	25.0	17.0	23.0	$\varnothing 0.8$
TL07-012	74	80	4	20.0	13.5	18.0	$\varnothing 0.8$
TL07-013	98	85	4	25.0	12.5	23.0	$\varnothing 0.8$
TL07-014	103	90	4	25.0	13.5	23.0	$\varnothing 0.8$
TL07-015	458	210	4	30.0	18.0	28.0	$\varnothing 0.8$
TL07-016	172	110	4	30.0	13.5	28.0	$\varnothing 0.8$
TL07-017	34	35	5	20.0	14.0	18.0	$\varnothing 1.0$
TL07-018	169	100	5	25.0	18.5	23.0	$\varnothing 1.0$
TL07-019	64	50	5	25.0	14.0	23.0	$\varnothing 1.0$
TL07-020	41	45	5	20.0	15.5	18.0	$\varnothing 1.0$
TL07-021	66	50	5	25.0	14.0	23.0	$\varnothing 1.0$
TL07-022	278	110	5	30.0	19.5	28.0	$\varnothing 1.0$
TL07-023	108	60	5	30.0	15.5	28.0	$\varnothing 1.0$
TL07-024	45	30	5	25.0	15.5	23.0	$\varnothing 1.2$
TL07-025	29	25	6	20.0	16.5	18.0	$\varnothing 1.2$
TL07-026	45	30	6	25.0	16.5	23.0	$\varnothing 1.2$
TL07-027	74	40	6	30.0	16.5	28.0	$\varnothing 1.2$
TL07-028	34	25	6	25.0	18.5	23.0	$\varnothing 1.4$
TL07-029	21	20	8	20.0	18.5	18.0	$\varnothing 1.4$
TL07-030	35	25	8	25.0	18.5	23.0	$\varnothing 1.4$
TL07-031	54	30	8	30.0	18.5	28.0	$\varnothing 1.4$
TL07-032	23	18	10	25.0	18.5	23.0	$\varnothing 1.6$
TL07-033	14	15	10	20.0	19.0	18.0	$\varnothing 1.6$
TL07-034	26	18	10	25.0	19.0	23.0	$\varnothing 1.6$
TL07-035	40	20	10	30.0	20.0	27.0	$\varnothing 1.6$